

REF.	MIN.	NOM.	MAX.	
Α	0.30	0.35	0.40	
A1	0.00	0.035	0.05	
A2	0.127 REF.			
А3		0.23		
р	1.15	1.20	1.25	
О	5.0 BSC			
Е	3.5 BSC			
Ф	2.1 BSC			
Г	4.75	4.80	4.85	
aaa	0.1			
bbb	0.1			

0.08

0.1

## NOTES:

- 1. ALL DIMENSIONS ARE IN MILLIMETERS. ANGLES ARE IN DEGREES.
- 2. DIMENSIONING & TOLERANCING CONFORM TO ASME Y14.5M-1994.
- $\sqrt{3}$ . COPLANARITY APPLIES TO LEADS, CORNER LEADS AND DIE ATTACH PAD.
- A MARKING SHOWN IS FOR PACKAGE ORIENTATION REFERENCE ONLY.
- 5. MATERIAL MUST COMPLY WITH BANNED AND RESTRICTED SUBSTANCES SPEC #10-0131.
- 6. ALL DIMENSIONS APPLY TO Pb FREE (+) PARTS.
- 7. PACKAGE CODE: S23A5N+1

	maxim integrated <sub>™</sub>		
TITLE: PACKAGE OUTL 2L SFN, 3.5x5			
APPROVAL	DOCUMENT CONTROL NO. 21-0661	rev. C	1/1

ddd

eee

-DRAWING NOT TO SCALE-