

NDTES:

- 1. ALL DIMENSIONING AND TOLERANCING CONFORM TO ANSI Y14.5-1982.
- 3. DIMENSIONS D1 AND E1 DO NOT INCLUDE MOLD PROTRUSION. ALLOWABLE MOLD PROTRUSION IS 0.25 MM ON D1 AND E1 DIMENSIONS.
- 4. THE TOP OF PACKAGE IS SMALLER THAN THE BOTTOM OF PACKAGE BY 0.15 MILLIMETERS.
- 5. DIMENSION & DOES NOT INCLUDE DAMBAR PROTRUSION. ALLOWABLE DAMBAR PROTRUSION SHALL BE 0.08 MM TOTAL IN EXCESS OF THE & DIMENSION AT MAXIMUM MATERIAL CONDITION.
- 6. ALL DIMENSIONS ARE IN MILLIMETERS.
- 7. THIS DUTLINE CONFORMS TO JEDEC PUBLICATION 95, REGISTRATION MS-026.
- 8. LEADS SHALL BE COPLANAR WITHIN .004 INCH.
- 9. EXPOSED DIE PAD SHALL BE COPLANAR WITH BOTTOM OF PACKAGE $_{\wedge}$ WITHIN 2 MILS (.05 MM).
- 10 MARKING IS FOR PACKAGE ORIENTATION REFERENCE ONLY.
- 11. MATERIAL MUST COMPLY WITH BANNED AND RESTRICTED SUBSTANCES SPEC # 10-0131.
- 12. ALL DIMENSIONS APPLY TO BOTH LEADED (-) AND PbFREE (+) PKG. CODES.

S Y M B L	DIMENSIONS	
	JEDEC AAA	
	MIN.	MAX.
А	_	1.20
A ₁	0.05	0.15
A2	0.95	1.05
D	6.80	7.20
D1	4.80	5.20
E	6.80	7,20
E1	4,80	5.20
L	0.45	0.75
Ν	32	
е	0.50 BSC.	
ø	0.17	0.27
b1	0.17	0.23
с	0.09	0.20
с1	0.09	0.16
PKG CDDE	H32-1, H32-2F, H32-3F, H32-4F	



-DRAWING NOT TO SCALE-