



## Product/Process Change Notice - PCN 09\_0120 Rev. -

Analog Devices, Inc. Three Technology Way Norwood, Massachusetts 02062-9106

This notice is to inform you of a change that will be made to certain ADI products (see Material Report). Any issues with this PCN or requirements to qualify the change (additional data or samples) must be sent to ADI within 30 days of publication date. ADI contact information is listed below.

**PCN Title:** ADM3251E Datasheet Specifications Change.  
**Publication Date:** 10-Aug-2009  
**Samples Available Date:** 17-Jul-2009  
**Effectivity Date:** 08-Nov-2009 *(the earliest date that a customer could expect to receive changed material)*

### Description Of Change

ADM3251E Primary Side Supply Input Current, ICC(DISABLE) under No load test conditions specification change:  
Current max limit is 1.5mA and this is being changed to 2.5mA.

### Reason For Change

Improved manufacturability

### Impact of the change (positive or negative) on fit, form, function & reliability

No impact on fit, form or reliability.

### Product Identification *(this section will describe how to identify the changed material)*

Parts after date code 0943 will be tested to the 2.5mA max spec.

### Summary of Supporting Information

These changes will be reflected in Rev A of the ADM3251E data sheet

**Supporting Documents** None

**For questions on this PCN, send email to the regional contacts below or contact your local ADI sales representative**

<b>Americas:</b>	PCN_Americas@analog.com	<b>Europe:</b>	PCN_Europe@analog.com	<b>Japan:</b>	PCN_Japan@analog.com
				<b>Rest of Asia:</b>	PCN_ROA@analog.com

Appendix A - Affected ADI Models	
Added Parts On This Revision - Product Family / Model Number (2)	
ADM3251E / ADM3251EARWZ	ADM3251E / ADM3251EARWZ-REEL

Appendix B - Revision History		
Rev	Publish Date	Rev Description
Rev. -	10-Aug-2009	ADM3251E Datasheet Specifications Table change.